

LINEAR REFLECTOR - LED

30/40 W



Applications | Store room | Power house | Control rooms |



PRODUCT SPECIFICATIONS

| Housing

Made of CRCA powder coated sheet with reflector
T8 tube made of extruded aluminium with polycarbonate
Diffuser

| light Source

High efficiency SMD LED mounted on MC PCB ,
LED efficacy > 150 lumens / watt

| Electrical

Powered by Inbuilt LED driver operates on wide voltage
window 145 to 275 V AC with APFC and Surge 2.5 kV
protection

SPECIAL FEATURES

- Suitable to install on surface / Wall and with suspension ropes
- High lumen delivers quality light
- Long life > 35,000 Hrs
- LM 80 certified LED light source
- Operates from 0 - 45 deg C

MODEL	POWER (W)	NOMINAL VOLTAGE (V)	CURRENT (l)	P.F	CCT & CCT (Ra)	SYSTEM LUMENS (Lm)	DIMENSIONS L/W/H (mm)
ELBT40R	40	230	0.19	> 0.9	5700 & > 0.8	3600	1200/290/150
ELBT30R	30	230	0.15	> 0.9	5700 & > 0.8	3600	1200/290/150

SPECIFICATIONS ARE SUBJECT TO CHANGE - POWER AND LUMENS TOLERANCE +/- 8 %